

160: Firefighting truck Double cabin, 4x4, Municipal type



CHASSES MAZ-5337 EQUIPPED WITH FIRE TANKER AC-5,5-40

PARAMETERS	DESCRIPTION
TRUCK FEATURES	Firefighting truck Double cabin, 4x4, Municipal type
LOAD PARAMETERS	
Gross mass of the truck, kg	17 700
DIMENSIONS (MM)	
Overall length	7 900
Overall width	2 550
Overall height	3 400

ENGINE:

Wheelbase

Power output, HP @ r.p.m. (min ⁻¹) Max torque, Nm @ r.p.m. (min ⁻¹)	270 hp @ 1900 min ⁻¹ 1128 Nm @ 1100-1500 min ⁻¹
Features	Diesel, 6 cylinder, V-type, turbo-supercharging and intercooler.
Displacement, l	11.15
Emission level	Euro 2, Euro 3
Fuel tank capacity, litre	200

3 9 5 0

DRIVE TRAIN

Clutch (type) Clutch control Gearbox Traction Drive axle's features STEERING	Dry single plate, plate diameter: 430 mm hydraulic drive, pneumatic booster Synchronized, 8 Forward/1Reverse gears 4 x 4 Rear, two-stage with the central reducer, interwheel differential lock and wheel cylindrical planetary type reducers. With the hydraulic booster. The control column is regulated on altitude, angle of declination, is supplied with
	anti-thief and trauma protection devices.
BRAKES Service:	Air pressure system, with drum type brake mechanisms, and ABS (antilock brake system)
Park:	With spring accumulators acting on rear wheels, air pressure charged.
ELECTRIC EQUIPMENT Features:	Single-wire, direct current with nominal voltage 24V. Includes 2 of 190 Amp hrs maintenance-free batteries. Alternator: 28V, 80A. Starter: 24V, 5,5kW
CABIN Features	All-metal, fixed on spring suspension, double-row, 6-seat, 4-door, can be tilted forward on 60° .
WHEELS AND TIRES:	14.00R20 – 4 wheels Spare wheel
FIREFIGHTING EQUIPMENT	
Volume of woter tank, l Volume of foam tank, l Pump:	5 000 240 Centrifugal fire pump

The manufacturer reserves the right to make modifications directed on improving of the automobile parameters.