



50: Truck with flatbed, 4x2, 3.0-5.5 t. crane optional



Photo of the base model MAZ-5336

PARAMETERS

DESCRIPTION

TRUCK FEATURES

Truck with flatbed, 4x2, 3,7 t, crane optional

LOAD PARAMETERS

Payload carried, kg:	3 700
Curb weight, kg	6 300
Gross mass of the truck, kg	10 100

DIMENSIONS (MM)

Overall length mm	8 200 mm
Overall width mm	2 550 mm
Overall height mm	3 100 mm
Wheelbase mm	4 200 mm

ENGINE:

Power output, HP @ r.p.m. (min^{-1})	155 hp @ 2400 min^{-1}
Max torque, Nm @ r.p.m. (min^{-1})	526 @ 1600 min^{-1}
Features	Diesel, 4 cylinder, L-type, turbo-supercharging and intercooler.
Displacement, l	4.75
Emission level	Euro 2, Euro 3. Simular Euro 4 & Euro 5 versions are available
Fuel tank capacity, litre	130

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) **Fax:** 1-647-933-9066 **E-mail:** info@mtzequipment.com **Web:** www.mtzequipment.com

DRIVE TRAIN

Clutch (type)	Dry single plate, plate diameter: 362 mm
Clutch control	hydraulic drive, pneumatic booster
Gearbox	Synchronized, 5 Forward/1Reverse gears
Traction	4 x 2
Drive axle's features	Rear, with the central conical reducer and differential lock.

STEERING

With the hydraulic booster. The control column is regulated on altitude, angle of declination, is supplied with anti-thief and trauma protection devices.

BRAKES

Service:	Air pressure system, with drum type brake mechanisms, with ABS (antilock brake system)
Park:	With spring accumulators having an effect on rear wheels, air pressure charged.

ELECTRIC EQUIPMENT

Features:	Single-wire, direct current with nominal voltage 24V. Includes 2 of 190 Amp·hrs maintenance-free batteries. Generator: 28V, 100A. Starter: 24V, 5,2kW.
-----------	--

CABIN

Features	All-metal, fixed on spring suspension, two-seat, two-door, can be tilted forward to secure engine service. Driver seat with pneumatic suspension. Additional folding-back sleeping place
----------	--

FLATBED

Dimensions, Length x Width , m	5300×2460mm
Wheels and Tires:	235/75R17.5, 6 wheels Spare wheel

The manufacturer reserves the right to make modifications directed on improvement of the automobile parameters.

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) **Fax:** 1-647-933-9066 **E-mail:** info@mtzequipment.com **Web:** www.mtzequipment.com

Crane (optional)



SPECIFICATION

Maximum loading capacity, kg	3 000
Load capacity at maximum outreach, kg	1 100
Maximum outreach, m	6,78
Maximum lift height, m	8,0
Control system	hydraulic

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) **Fax:** 1-647-933-9066 **E-mail:** info@mtzequipment.com **Web:** www.mtzequipment.com