



56: Truck with flatbed, 6x4, payload min 12.0, crane optional



Photo of the base model.

PARAMETERS

DESCRIPTION

TRUCK FEATURES

Truck with flatbed, 6x4, payload 11.3 t, crane optional
Payload 12 t optional

LOAD PARAMETERS

Payload carried, kg:	11 300
Curb weight, kg	13 200
Gross mass of the truck, kg	24 500

DIMENSIONS (MM)

Overall length, mm	10 230
Overall width, mm	2 550
Overall height, mm	4 000
Wheelbase, mm	4 590

ENGINE:

Power output, HP @ r.p.m. (min^{-1})	330 hp @ 2000 min^{-1}
Max torque, Nm @ r.p.m. (min^{-1})	1274 Nm @ 1100-1300 min^{-1}
Features	Diesel, 8 cylinder, V-type, turbo-supercharging and intercooler.
Displacement, l	14.86
Emission level	Euro 2, Euro 3 Similar Euro 4 & Euro 5 versions are available
Fuel tank capacity, litre	350

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) **Fax:** 1-647-933-9066 **E-mail:** info@mtzequipment.com **Web:** www.mtzequipment.com

DRIVE TRAIN

Clutch (type)	Dry single plate, plate diameter: 430 mm
Clutch control	hydraulic drive, pneumatic booster
Gearbox	Synchronized, 8 Forward/1Reverse gears
Traction	6 x 4
Drive axle's features	Rear and middle, two-stage with the central reducer, Interwheel and interaxle differential locks and wheel cylindrical planetary type reducers.

STEERING

With the hydraulic booster. The control column is regulated on altitude, angle of declination, is supplied with anti-thief and trauma protection devices.

BRAKES

Service:	Air pressure system, with drum type brake mechanisms, and ABS (antilock brake system)
Park:	With spring accumulators acting on rear wheels, air pressure charged.

ELECTRIC EQUIPMENT

Features:	Single-wire, direct current with nominal voltage 24V. Includes 2 of 190 Amp·hrs maintenance-free batteries. Alternator: 28V, 80A. Starter: 24V, 5,5kW.
-----------	--

CABIN

Features	All-metal, fixed on spring suspension, two-seat, two-door, can be tilted forward to secure engine service. Driver Seat with pneumatic suspension. Equipped with sleeping place
----------	--

FLATBED

Dimensions, Length x Width, m	6150×2480mm
-------------------------------	-------------

Wheels and Tires:

11.00R20 or 315/80R22.5 – 10 wheels.
Spare wheel

The manufacturer reserves the right to make modifications directed on improvement of the automobile parameters

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) **Fax:** 1-647-933-9066 **E-mail:** info@mtzequipment.com **Web:** www.mtzequipment.com

Crane (optional)



SPECIFICATION

Maximum loading capacity, kg	3 000
Load capacity at maximum outreach, kg	1 100
Maximum outreach, m	6,78
Maximum lift height, m	8,0
Control system	hydraulic

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) **Fax:** 1-647-933-9066 **E-mail:** info@mtzequipment.com **Web:** www.mtzequipment.com