

# 60: Truck with potable water tank, 4x2, capacity min. 8000 litre



# Photo of the base model MAZ-5337

### **PARAMETERS**

### **DESCRIPTION**

**TRUCK FEATURES** Truck with potable water tank, 4x2, capacity min. 8000 l.

## LOAD PARAMETERS

Payload carried, kg:	7 930
Curb weight, kg	8 570
Gross mass of the truck, kg	16 500

### **DIMENSIONS (MM)**

Overall length, mm	6 900
Overall width, mm	2 550
Overall height, mm	2 900
Wheelbase, mm	3 950

#### **ENGINE:**

Power output, HP @ r.p.m. (min<sup>-1</sup>) 230 hp @ 2100 min<sup>-1</sup>

Max torque, Nm @ r.p.m. (min<sup>-1</sup>) 882 Nm @ 1100-1300 min<sup>-1</sup>

Features Diesel, 6 cylinder, V-type, turbo-supercharging and

intercooler.

Displacement, l 11.25

Emission level Euro 2, Euro 3

Fuel tank capacity, litre 200

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) Fax: 1-647-933-9066 E-mail: info@mtzequipment.com Web: www.mtzequipment.com

#### **DRIVE TRAIN**

Clutch (type) Dry single plate, plate diameter: 430 mm
Clutch control hydraulic drive, pneumatic booster
Gearbox Synchronized, 5 Forward/1Reverse gears

Traction 4 x 2

Drive axle's features Rear, two-stage with central reducer and wheel cylindrical

transmissions of planetary type, with differential

interwheel lock.

**STEERING** With the hydraulic booster. The control column is

regulated on altitude, angle of declination, is supplied with

anti-thief and trauma protection devices.

**BRAKES** 

Service: Air pressure system, with drum type brake mechanisms,

and ABS (antilock brake system)

Park: With spring accumulators acting on rear wheels, air

pressure charged.

**ELECTRIC EQUIPMENT** 

Features: Single-wire, direct current with nominal voltage 24V.

Includes 2 of 190 Amp·hrs maintenance-free batteries.

Alternator: 28V, 80A. Starter: 24V, 5,5kW.

**CABIN** 

Features All-metal, fixed on spring suspension, two-seat, two-door,

can be tilted forward on  $60^{\circ}$  to secure engine service.

Wheels and Tires: 12.00R20–6 wheels.

Spare wheel.

The manufacturer reserves the right to make modifications directed on improvement of the automobile

parameters

Tel: 1-855-2GO-4MTZ (1-855-246-4689) Fax: 1-647-933-9066 E-mail: info@mtzequipment.com Web: www.mtzequipment.com