

61: Truck with potable water tank, 6x4, capacity min. 16.000 litre



Photo of the base model MAZ-6303

PARAMETERS

DESCRIPTION

TRUCK FEATURES

Truck with potable water tank, 6x4, capacity 12000 l standard, (16 000 option)

LOAD PARAMETERS

Payload carried, kg:	12 000 (16 000 option)
Curb weight, kg	12 500
Gross mass of the truck, kg	24 500

DIMENSIONS (MM)

Overall length, mm9 690Overall width, mm2 550Overall height, mm3 130Wheelbase, mm4 590

ENGINE:

Power output, HP @ r.p.m. (min ⁻¹) Max torque, Nm @ r.p.m. (min ⁻¹)	330 hp @ 2100 min ⁻¹ 1274 Nm @ 1100-1300 min ⁻¹
Features	Diesel, 6 cylinder, V-type, turbo-supercharging and
	intercooler.
Displacement, l	14.86
Emission level	Euro 2, Euro 3
Fuel tank capacity, litre	350

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada Tel: 1-855-2GO-4MTZ (1-855-246-4689) Fax: 1-647-933-9066 E-mail: info@mtzequipment.com Web: www.mtzequipment.com

DRIVE TRAIN

Clutch (type) Clutch control Gearbox Traction Drive axle's features	Dry single plate, plate diameter: 430 mm hydraulic drive, pneumatic booster Synchronized, 8 Forward/1Reverse gears 6 x 4 Rear and middle, two-stage with the central reducer, Interwheel and interaxle differential locks and wheel cylindrical planetary type reducers
STEERING	With the hydraulic booster. The control column is regulated on altitude, angle of declination, is supplied with anti-thief and trauma protection devices.
BRAKES Service:	Air pressure system, with drum type brake mechanisms, and ABS (antilock brake system)
Park:	With spring accumulators acting on rear wheels, air pressure charged.
ELECTRIC EQUIPMENT Features:	Single-wire, direct current with nominal voltage 24V. Includes 2 of 190 Amp hrs maintenance-free batteries. Alternator: 28V, 80A. Starter: 24V, 5,5kW.
CABIN Features	All-metal, fixed on spring suspension, two-seat, two-door, can be tilted forward to secure engine service. Driver Seat with pneumatic suspension. Equipped with sleeping place
Potable water tank	$V=12 \text{ m}^3$ (16 m ³ option).
Wheels and Tires:	11.00R20 or 315/80R22.5 – 10 wheels Spare wheel
The manufacturer reserves the right to make modifications directed on improvement of the automobile parameters.	