



70: Truck with cesspool, 4x2, capacity min. 5500 litre



Photo of the base model MAZ-592002-390 on chasses MAZ-5337

PARAMETERS

DESCRIPTION

TRUCK FEATURES

Truck with cesspool, 4x2, capacity 8700 l.

LOAD PARAMETERS

Payload carried, kg:	9 000
Curb weight, kg	9 000
Gross mass of the truck, kg	18 000

DIMENSIONS (MM)

Overall length, mm	7 400 mm
Overall width, mm	2 550 mm
Overall height, mm	3 300 mm
Wheelbase, mm	3 950 mm

ENGINE:

Power output, HP @ r.p.m. (min^{-1})	230 hp @ 2100 min^{-1}
Max torque, Nm @ r.p.m. (min^{-1})	882 Nm @ 1100-1300 min^{-1}
Features	Diesel, 6 cylinder, V-type, turbo-supercharging and intercooler.
Displacement, l	11.15
Emission level	Euro 2, Euro 3
Fuel tank capacity, litre	200

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) **Fax:** 1-647-933-9066 **E-mail:** info@mtzequipment.com **Web:** www.mtzequipment.com

DRIVE TRAIN

Clutch (type)	Dry single plate, plate diameter: 430 mm
Clutch control	hydraulic drive, pneumatic booster
Gearbox	Synchronized, 5 Forward/1Reverse gears
Traction	4 x 2
Drive axle's features	Rear, two-stage with central reducer and wheel cylindrical transmissions of planetary type, with differential interwheel lock.

STEERING

With the hydraulic booster. The control column is regulated on altitude, angle of declination, is supplied with anti-thief and trauma protection devices.

BRAKES

Service:	Air pressure system, with drum type brake mechanisms, and ABS (antilock brake system)
Park:	With spring accumulators acting on rear wheels, air pressure charged.

ELECTRIC EQUIPMENT

Features:	Single-wire, direct current with nominal voltage 24V. Includes 2 of 190 Amp·hrs maintenance-free batteries. Alternator: 28V, 80A. Starter: 24V, 5,5kW.
-----------	--

CABIN

Features	All-metal, fixed on spring suspension, two-seat, two-door, can be tilted forward on 60° to secure engine service.
----------	---

CESSPOOL

V=8.7 m³.
Cesspool is designated for vacuum separation of sinkholes and drain shafts.

Wheels and Tires:

12.00R20– 6 wheels.
Spare wheel.

The manufacturer reserves the right to make modifications directed on improvement of the automobile parameters.

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) **Fax:** 1-647-933-9066 **E-mail:** info@mtzequipment.com **Web:** www.mtzequipment.com