

Wheel loader MTZ K-702MA-PK6



Wheel loader MTZ K-702MA-PK6 used in loading and unloading materials without preliminary loosening. The loader can be used in construction, agriculture, reclamation. Key features:

- High efficiency;
- Generality;
- Developed and tested design;
- High durability of bearing elements;
- Excellent maintainability;
- Safety;
- Reliable local and foreign component parts;
- Suitable for operation in harsh conditions (possibility to upgrade for operation in North condition

Technical characteristics

Power Output HP at rpm,	235
Wheel loader capacity	3.5 m3
No. of cylinders,	8
Displacement, cubic centimeters, cc	14860
Fuel	Diesel
No. of speeds, min. or hydrostatic	8, consisting the torque converter
Steering	articulated
Top speed, km/h	39
Transmission	Power Shuttle Transmission*, 4Fx3R
Rated Bucket Capacity, m3	3,5
Bucket width, mm,	3100
Reach with lift arms horizontal, mm,	2930
Digging Depth, mm, min.	600
Overall hight at full raise, mm	5690

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) Fax: 1-647-933-9066 E-mail: info@mtzequipment.com Web: www.mtzequipment.com

3260
320
Yes
Yes
Yes
Yes
24v
31,72
Tier 0
8,3
29,5/75R25, PR 3kg/sm2
29,5/75R25, PR 3kg/sm2
420
8900x3100x3800
21000
English.
Spanish, Franch & Arabic available on
request
Yes
3-14

* Mechanical, with hydraulic transformer