

Farm tractor -min. 45 HP - 2WD Belarus MTZ-510



The tractor is designed for various agricultural operations with mounted, semi-mounted and trailed machines and implements, for transport operations.

Capacity, h.p./kW57/41,9Axle arrangement4K2Number of gears FWD/BWD 9/2

Technical characteristics

Engine	
Туре	without turbocharging
Capacity, h.p./kW	57/41,9
Brand mark	D-244
Fuel use, g/(kW·h)	229,0 ^{+6,9}
Torque capacity, H·m ²	271
Transmission system	
Selective gear	manual, with reducing gear that doubles the number of gears
Flywheel clutch	single-disk, friction, spring-loaded
Number of gears FWD/BWD	9/2
Back PTO shaft, min ⁻¹	540
Hydraulics	
Load-carrying capacity of back suspension gear on suspension axis, kg, minimum	3200
Full scale pressure, MPa	20-2
Pump displacement at nominal speed of diesel crankshaft, I/min, minimum	45

Undercarriage

Туре	wheeled
Axle arrangement	4K2
Maximum weight, kg	5800
Tyres	
front	7.50-20/9.00-20
back	15.5R38/18.4R30/9.50-42
Climatic modification	У1/Т1
Minimum and maximum speed FWD/BWD, km/h	Min 1,44/3.18 Max 26,50/7,10