



3 Furrow Plough PLN 3-35

Plow PLN-3-35 is designed for plowing soils with specific resistance to 0.9 kg/cm² at a depth of 30 cm.

Intended to operate with 80-100 hp tractors, such as MTZ/Belarus 80,82, 820, 920, 952 etc.

Requirements for the soil: without stones, fieldstone and other obstacles, with specific resistance to 0.12 MPa (1.2 kg / cm²), the hardness of 4 MPa (40 kg / cm²) and the humidity to 22%.



Main advantages:

- Polymer coating, resistant to elements
- High strength steel is used for working parts
- Modular assembly, allowing to replace only the failed part
- Special design and geometry allow for optimal removal of weeds

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) **Fax:** 1-647-933-9066 **E-mail:** info@mtzequipment.com **Web:** www.mtzequipment.com

Specifications

The method of aggregation	hinged
Performance for 1 hour, ha / h	up to 0,995
Working speed, km / h	9
Width, m	1.05
Weight, kg	454 ± 3%
Processing depth, cm	30
Dimensions (in working position), mm	
Length	2730 ± 100
Width	1370 ± 30
Height	1200 ± 30
The distance from the reference plane to the bottom plane of the frame, at least, mm	620
The number of working parts, pieces.	3
Depth of processing colter see	12
Service life, years	8

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) **Fax:** 1-647-933-9066 **E-mail:** info@mtzequipment.com **Web:** www.mtzequipment.com