



Rotary mower, min. 1.6 m width - Disc-mounted mower KDN-210



<i>Specifications</i>	<i>Value</i>
Constructive width of cut, m	2.1±0.02
Control height of cut, mm	40-100
Operating speed, km/h	5-15
Transport speed, km/h, no more	25
Weight, kg	530±16
Mower outline dimensions in operation position, mm, no more	
- length	3590
- width	1600
- height	1400
Mower outline dimensions with tractor MTZ-80 in the transport position, mm, no more:	
- length	5250
- width	3000
- height	2600
Road clearance, mm, not less than	280
Operation pressure in hydrosystem, MPa, no more	16
Mower capacity, ha/hour:	
- basic time	0.95-2.85
- operation time	0.55-1.75
Power demand from tractor PTS, kW, no more	20
Specific mass on meter of constructive width of cut, kg/m	252±8
Losses, %, no more	1
Safety factor technical process, not loss than	0.99

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) **Fax:** 1-647-933-9066 **E-mail:** info@mtzequipment.com **Web:** www.mtzequipment.com