



Baler PT-165M

(Square baler PT-165M)



<i>Specifications</i>	<i>Value</i>
Baler type	tractor-mounted
Weight (without SPTA), kg, not more	1600±30
Overall dimensions, mm, not more	
- length	4120
- transport width	2725
- height	1634
Operating speed, km/h	6-10
Travelling speed, km/h, not more	15
Baler structural pick-up width, mm	1650±25
Gauge width, mm	2280±25
Road clearance, mm, not less	230
Operating pressure in the hydraulic system, MPa, not more	16,0
Tyres	
- right	5.50-16 (FBeI-256)
- left	13.00/75-16
Compression chamber section , mm	
- width	460 ⁺⁵
- height	360 ⁺⁵
Number of pistons strokes per minute, at rotating speed of PTO, 9 s ⁻¹	100
Inlet opening content, mm ²	1430±25
Towing ring size, mm, DxS according to GOST 13398-82	40 ⁺³ ×30±2

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) **Fax:** 1-647-933-9066 **E-mail:** info@mtzequipment.com **Web:** www.mtzequipment.com

Baling capacity, not less than	98%
Bale weight max, kg, with length of 1,0 m - on hay at moisture content (20-22)% - on straw at moisture content (10-20)%	33 26,5
Baling density, kg/m ³ , adjustable - on hay at moisture content (20-22)% - on straw at moisture content (10-20)%	150-200 110-150
Unbound bales, not more	3,5%
Capacity per 1 hour of operation time, t, not less (at the operating speed of not less than 6 km/h and the bale density of not less than 1,2 kg/m) - on hay at moisture content (20-22)% - on straw at moisture content (10-20)%	7,7 5,5

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) **Fax:** 1-647-933-9066 **E-mail:** info@mtzequipment.com **Web:** www.mtzequipment.com