

Crawler tractor tracked min.180hp - Belarus MTZ-2103



The agricultural track-type tractor is intended for work in agriculture with hinged, semi-hinged, hook-on cars, including for works of general purpose on the dehumidified soils.

Capacity Selective gear Number of gears FWD/BWD 156 kW (212 hp) Hydromechanical 16/8

Technical characteristics

| Nominal traction force, kN | 40 |
|--|---|
| Overall dimensions (length/width/height), mm | 6250/2100/2950 |
| Travel speed (forward/reverse), km/h | 3,08–26,12/4,21–14,47 |
| Ground clearance, mm | 360 |
| Engine | |
| Туре | 4-stroke, diesel, six-cylinder, line, liquid cooling with a turbo-supercharging and intermediate cooling of air |
| Capacity, kW (h.p.) | 156 (212) |
| Brand mark | MMZ D-260.4S2 |
| Ecological standard | Tier II |
| Fuel rate at rated power, g/kW·h | 227 |
| Transmission system | |
| Flywheel clutch | dry, two-disk |
| Selective gear | mechanical, step, with gear shifting under loading |
| Number of gears FWD/BWD | 16/8 |
| Back PTO shaft | independent II, rpm |
| | |

Hydraulics

| Туре | separate and modular with the opened circulation and a full-line filtration of working liquid |
|--|---|
| Quantity of conclusions of a hydraulic system | four couples |
| Pressure of setup of the safety valve of a hydraulic system, MPa | 20,0 |
| Hydraulics reservoir capacity, l | 70 |
| Other specifications | |
| Type of the back hinged device | NY-3 GOST 10677 |
| Loading capacity on an axis of hinges of the lower drafts, kg | 8000 |
| | |

Additional options

- metal track-type with rubber-metal hinges
- heater