

# Roller vibrating padded drum soil Belarus AMKODOR 6712BB



## Single Drum Vibrating Roller

### AMKODOR 67128B

The roller is equipped with soil compaction degree device. It is possible to install removable cam fread. Single drum vibrating roller is designed for stabilized soils, road bases compaction, for gravel-sandy mixtures during fill constructions of rail and motor roads, during dike, dam, airfield and other soil constructions, layer-by-layer sandy, macrofragmental and loose soil compaction. Depths of compaction (active zone) are: dust-like soil – 0,35-

 $0.5\,\text{m}$ ; sand and gravel – 0.5 -  $0.7\,\text{m}$ ; rocky soil – 0.9 -  $1.5\,\text{m}$ ; clay compaction with the help of cam tread – 0.3 -  $0.6\,\text{m}$ .

For safety's sake engine start inhibit is installed to the roller when propel control lever is not in neutral position. The roller is equipped with 3 brake systems: service, reserve and parking which work separately. All brake systems are run from the operator's seat. All compactors as well as vibrating soil compactors provide quick excess to the engine, hydro systems and lubrication points and filters. It simplifies operator's work and provides machine reliability.

#### Technical specifications:

## AMKODOR 6712BB

Туре	Vibrating self-propelled
Operating weight, kg	12 100
Orum	Smooth vibrating
Compaction width, mm	2 100
Orum diameter, mm	1 500
√ibrator drive	Hydrostatic
Oriving force, kN	232/148
Vibration frequency, hz	28/32
Amplitude, mm	1.77/0.97
ine pressure, kg/cm	28.6
Wheels number	2
Fires Fires	21.3-R24
Engine	D-245
Cooling system	water
Engine power	77 kW (105 HP) at 2200 rpm
Steering	Articulated frame with hydraulic drive and hydraulic
	feed-back
Semi-frames articulation angle, deg	±30
Min turning radius, mm	7 000
Orive	Hydrostatic
Speed, forward/reverse, km/h:	
pperating	0-6.6/0-6.6
ravel	0-13.2/0-13.2
Service brakes	Closed loop of hydrostatic drive
Parking brakes	Multi- disk closed oil-immersed brakes, hydraulically
	released, built in travelling pumps
ength, mm	5 800
Nidth, mm	2 320
Height, mm	3 570
Height over cabin without flashlight, mm	3 385

Head Office: 3-1136 Centre St, Ste. 124, Thornhill, ON, L4J 3M8, Canada Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2, Canada

Tel: 1-855-2GO-4MTZ (1-855-246-4689) Fax: 1-647-933-9066 E-mail: info@mtzequipment.com Web: www.mtzequipment.com