


MTZ Tractors Made in BELARUS

MTZ 1221 (136 hp)

- Loaded with extra features as part of the standard package
- Heaviest tractor in it's class, with largest 3 pt hitch capacity
- 4WD - Auto and full lockup modes
- Durable, reliable engine (no DEF, no DPF, no computers)
- Bar axles for rear wheels space adjustment
- PTO modes: 540/1000 / Ground speed / Disengaged
- Dedicated steering system
- 6 Cylinder
- Long stroke, low rev engine rated for 10,000+ hours
- Economical on fuel
- Service does not require any specialized tooling
- MTZ - World's largest exporter of Tractors



Operator's Station



Available bi-directional package
(2nd set of controls for reverse driving)



Available front hitch
and PTO package

• **Durable** • **Reliable** • **Affordable**

• Durable • Reliable • Affordable

MTZ 1221

STANDARD FEATURES - MTZ 1221 Tractors come equipped with Cab including: AC, heater, joystick, inside & outside mirrors, front and rear windshield wipers • Dedicated steering system • Block heater • Lights included: headlights (hi & low beam), 4 front & 2 rear work lights, brake lights, turn indicators and 4 way flashers • 3 remote hydraulic valves (2 are joystick controlled) • Quick change PTO shaft • 4WD has 3 selections • Front and Rear radial tires • Front Fenders • Front weights + weight carrier • Air Compressor, for cleaning radiator in the field, inflating tires etc. • Complete PDI (Pre Delivery Inspection) - Field Ready

SPECIFICATIONS

Engine	
Manufacturer	Minsk Motor Plant, Belarus
Model	D-260.2S3A
Horsepower	136 Engine 125 PTO
Displacement	7.12L (435 cu. in.)
Rated Speed RPM	2100
Cylinder	6
Diesel	Direct injection
Aspiration	Turbocharged
Air compressor + hose	Standard
Electric Equipment	
Alternator	12V 1,150 W
Starter rated voltage	24 v, 5,500 W
Transmission Options	
Type	① Partial Power Shift - 16F / 8R ② Synchronised - 16F / 8R
Speed Range	Forward: 1.74 to 32.57 km/h (1.08 to 20.23 mph) Reverse: 2.73 to 15.61 km/h (1.69 to 9.69 mph)
Type	③ Synchronised - 24F / 12R
Speed range	Forward: 1.7 to 36.3 km/h (1.06 to 22.6 mph) Reverse: 2.5 to 17.1 km/h (1.55 to 10.62 mph)
Creeper - Optional	Min. speed Forward: 0.38 km/h (0.24 mph) Reverse: 0.60 km/h (0.37 mph)
4WD	
Front Axle	Straight front axle
Type	Planetary Spur Reduction Gears
Control modes	Off / Always on / Automatic Safety clutch protection
Rear Axle	Bar type
Adjustable hubs	Tapered cone style
Differential	Off / Always on / Automatic

Clutch	Dual, Dry Disk
PTO	
Type	Mechanical independent live
Speeds	540/1000 / Ground speed
Brakes	Oil immersed
Hydraulic System	Live, open centre, gear type pump
Pump Capacity	56 L/min (15 Gal./min)
Hydrostatic power steering	14 L.min (3.6 Gal./min)
Remote valves	3; 2 are Joystick controlled
Draft control	Mechanical
3 point hitch	Category II with Linkage stabilizers
Lift capacity @ hitch point	4,300 kg (9,555 lb.)
Cab	Heat and Air Conditioning
2 Doors	Flat Platform
Seat suspension	Mechanical
	Optional Grammer Seat
Capacities	
Fuel Tank	2 tanks 270 L (71 gal) or 1 tank 140 L (37 gal.)
Hydraulic System	45 L (11.8 gal.)
Tires	
Front	420 / 70R24
Rear	18.4R38
Dimensions	
Wheelbase	2.6 m (8.5')
Overall Length	4.6 m (15.1')
Overall Width	2.3 m (7.5')
Height to Top of Cab	2.89 m (9.5')
Clearance	0.63 m (2.1')
Turning Radius	4.49 m 14.7'
Fordable depth	0.85 m (2.8')
Weights	
Weight (operational)	4,300 kg (12,170 lbs.)



Head Office: 3-1136 Centre St., Ste. 124, Thornhill, Ontario, L4J 3M8 Canada
 Tel: 1-855-2GO-4MTZ (1-855-246-4689) Fax: 1-647-933-9066
 E-mail: info@mtzequipment.com Web: www.mtzequipment.com

Warehouse: 2682 Highway 34, Hawkesbury, Ontario, K6A 2R2 Canada