


MTZ Tractors Made in BELARUS

MTZ 2022 (212 hp)

- Loaded with extra features as as part of the standard package
- Heaviest tractor in it's class, with largest 3 pt hitch capacity
- 4WD - Auto and full lockup modes
- Durable, reliable engine (no DEF, no DPF, no computers)
- Bar axles with tapered con habs
- PTO modes: 540/1000 / Ground speed / Disengaged
- Dedicated steering system
- Long stroke, low rev engine rated for 10,000+ hours
- Economical on fuel
- Service does not require any specialized tooling
- MTZ - World's largest exporter of Tractors



Operator's Station



Available bi-directional package
(2nd set of controls for reverse driving)



Available front hitch
and PTO package

• **Durable** • **Reliable** • **Affordable**

• Durable • Reliable • Affordable

MTZ 2022

STANDARD FEATURES - MTZ 2022 Tractors come equipped with Cab including: AC, heater, inside & outside mirrors, front and rear windshield wipers • Dedicated steering system • Block heater • Lights included: headlights (hi & low beam), 4 front & 4 rear work lights, brake lights, turn indicators and 4 way flashers • 3 remote hydraulic valves • Quick change PTO shaft • 4WD has 3 selections • Front and Rear radial tires • Front Fenders • Front weights + weight carrier • Air Compressor for cleaning radiator in the field, inflating tires etc. • Complete PDI (Pre Delivery Inspection) - Field Ready.

SPECIFICATIONS

Engine	
Manufacturer	Minsk Motor Plant, Belarus
Model	D-260.4S3A
Horsepower	212 Engine 195 PTO
Displacement	7.12L (434.5 cu. in.)
Rated Speed RPM	2100
Cylinder	6
Diesel	Direct injection
Aspiration	Turbocharged
Air compressor + hose	Standard
Electrical Equipment	
Alternator	12V 2,000 W
Starter rated voltage	24V 5,900 W
Clutch	Dual, Dry Disk
Transmission	
Type	① Partial Power Shift - 16F / 8R
Speed Range	Forward: 1.74 to 32.57 km/h (1.08 to 20.23 mph) Reverse: 2.73 to 15.61 km/h (1.69 to 9.69 mph)
Type	② Synchronised - 24F / 12R
Speed range	Forward: 1.7 to 36.3 km/h 1.06 to 22.6 mph) Reverse: 2.5 to 17.1 km/h (1.55 to 10.62 mph)
4WD	
Front Axle	Straight front axle
Type	Planetary Spur Reduction Gears
Control modes	Off / Always on / Automatic Safety clutch protection
Rear Axle	Bar Type
Adjustable hubs	Tapered cone style
Differential	Off / Always on / Automatic

PTO	
Type	Multi-disc independent live
Speeds	540/1000 / Ground speed
Brakes	Multi-disc, Oil immersed
Hydraulic System	
Pumping Capacity	Live, open centre, gear type pump 55 L/min (14.5 Gal./min)
Hydrostatic power steering	14 L.min (3.6 Gal./min)
Remote valves	3
Draft control	Electrical
3 point hitch	Category 3 with Linkage stabilizers
Lift capacity @ hitch point	6500 kg (14,330 lb.)
Cab	
2 Doors	Heat and Air Conditioning
Seat suspension	Flat Platform Mechanical Optional Grammer Seat Optional Trainer Seat
Capacities	
Fuel Tank	2 Tanks, total 357 L (94.3 gal.)
Hydraulic System	45 L (11.8 gal.)
Tires	
Front	420 / 70R24
Rear	580 / 70R42
Dimensions	
Wheelbase	2.92 m (9.6')
Overall Length	5.23 m (17.2')
Height to Top of Cab	3.12 m (10.3')
Clearance	0.54 m (1.77')
Turning Radius	5.3 m (17.3')
Fordable depth	0.85 m (2.8')
Weights	
Weight (operational)	7,220 kg (15,917 lbs.)



Head Office: 3-1136 Centre St., Ste. 124, Thornhill, ON, L4J 3M8 Canada
 Tel: 1-855-2GO-4MTZ (1-855-246-4689) Fax: 1-647-933-9066
 E-mail: info@mtzequipment.com Web: www.mtzequipment.com

Warehouses: Canada - 2682 Highway 34, Hawkesbury, ON, K6A 2R2, Canada
 USA - 2001 West Interstate 30, Sulphur Springs, TX, 75482, USA