

MTZ Tractors Made in BELARUS

MTZ 920 (84 hp) / MTZ 952 (105 hp)

- Loaded with extra features as part of the standard package
- Heaviest tractor in it's class, with largest 3 pt hitch capacity
- 4WD - Auto and full lockup modes
- Durable, reliable engine (no DEF, no DPF, no computers)
- 4WD - front end protected by safety clutch
- Bar axle for rear wheels space adjustment
- PTO modes: 540/1000 / Ground speed / Disengaged
- Dedicated steering system
- Long stroke, low rev engine rated for 10,000+ hours
- Economical on fuel
- Service does not require any specialized tooling
- MTZ - World's largest exporter of Tractors



Heaviest tractor in it's class with largest 3 pt hitch capacity



PTO modes: 540/1000 / Ground Speed / Disengage



Available with self-leveling loader

• **Durable** • **Reliable** • **Affordable**

• **Durable** • **Reliable** • **Affordable**

MTZ 920 / MTZ 952

STANDARD FEATURES - MTZ 920 and MTZ 952 Tractors come equipped with Cab including: AC, heater, joystick, inside & outside mirrors, front and rear windshield wipers • Dedicated steering system • Block heater • Lights included: headlights (hi & low beam), 4 front & 2 rear work lights, brake lights, turn indicators and 4 way flashers • 3 remote hydraulic valves (2 are joystick controlled) • Quick change PTO shaft • 4WD has 3 selections • Front and Rear radial tires • Front Fenders • Front weights + weight carrier • Air Compressor, for cleaning radiator in the field, inflating tires etc. • Complete PDI (Pre Delivery Inspection) - Field Ready

SPECIFICATIONS

Engine	920	952
Manufacturer	Minsk Motor Plant, Belarus	
Model	D-245.43S3AM	D245.5S3AM
Horsepower*	84 Engine	105 Engine
	77 PTO	95 PTO
Displacement	4.75L (290 cu. in.)	
Rated Speed	1800 RPM	
Cylinder	4	
Diesel	Direct injection	
Aspiration	Turbocharged	
Air compressor + hose	Standard	
Electrical Equipment		
Alternator	12V 1,000 W	
Starter rated voltage	24 v	
Clutch	Single, Dry Disk	
Transmission		
Type	Synchronised Speed	
Gears (Standard)	14 forward, 4 reverse	
(Optional)	Mechanical Shuttle	
	7 forward, 7 reverse + shifter	
Speed range	Forward: 2.19 to 39.7 km/h (1.36 to 24.7 mph)	
	Reverse: 4.60 to 8.36 km/h (2.85 to 5.20 mph)	
Creeper	Optional, Min. speed 0.6 km/h	
4WD		
Front Axle	Straight front axle	
Type	Planetary Spur Reduction Gears	
Control modes	Off / Always on / Automatic	
	Safety clutch protection	
Rear Axle	Bar type	
Adjustable hubs	Tapered cone style	
Differential	Off / Always on / Automatic	

PTO	
Type	Mechanical independent live
Speeds	540/1000 / Ground speed
Brakes	Mechanical dry disc type Optional oil immersed
Hydraulic System	Live, open centre, gear type pump
Pump Capacity	45 L/min (12 Gal./min)
Hydrostatic power steering	14 L.min (3.6 Gal./min)
Remote valves	3; 2 are Joystick controlled
Draft control	Mechanical
3 point hitch	Category II with Linkage stabilizers
Lift capacity @ hitch point	4,000 kg (8,820 lb.)
Cab	Heat and Air Conditioning
2 Doors	Flat Platform
Seat suspension	Mechanical Optional Grammer Seat
Capacities	
Fuel Tank	135 L (35.6 gal.)
Hydraulic System	45 L (11.8 gal.)
Tires	
Front	360 / 70R24
Rear	18.4R34
Dimensions	
Wheelbase	2.45 m (8.0')
Overall Length	4.44 m (14.6')
Height to Top of Cab	2.85 m (9.4')
Clearance	0.51 m (1.7')
Turning Radius	4.50 m (14.8')
Fordable depth	0.85 m (2.8')
Weights	
Weight (operational)	4,300 kg (9,480 lbs.)



Head Office: 3-1136 Centre St., Ste. 124, Thornhill, ON, L4J 3M8 Canada
 Tel: 1-855-2GO-4MTZ (1-855-246-4689) Fax: 1-647-933-9066
 E-mail: info@mtzequipment.com Web: www.mtzequipment.com

Warehouses: Canada - 2682 Highway 34, Hawkesbury, ON, K6A 2R2, Canada
 USA - 2001 West Interstate 30, Sulphur Springs, TX, 75482, USA