



### Annotation:

The present operational bulletin contains modified data on operation of BELARUS-80.1/82.1/82.2/82P completed with a distributor ПИ70 with one valve fixed in “Uplift” position.

### Content of changes:

1 Unit “2. General description and technical specifications of tractors”, subsection “2.2 General technical data”, “Hydraulic lift linkage” shall amended as follows:

- the information available: “Valve distributor P80-3/4-222/111 for tractors with a draft control unit, P80-3/1-222 for tractors without a draft control unit;
- shall be replaced with: “Valve distributor P80-3/4-222/111 or ПИ70-1221C for tractors with a draft control unit; P80-3/1-222 or ПИ70-890 for tractors without a draft control unit”.

2 In Unit “4. Controls and instruments”, subsection “4.1 Controls of a tractor with a modular cab” the descriptions 27, 28, 29 shall be supplemented with the following text:

“At the “Uplift” position on distributors P80-3/4-222 and P80-3/1-222 the levers are fixed and automatically return to “Neutral” position with the pressure from 16,5 to 20 MPa; on distributors P80-3/4-111, ПИ70-1221C and ПИ70-890 the levers do not get fixed and return to “Neutral” position.

Against order the tractors may be equipped with a distributor ПИ70 with fixation of a valve, controlling right side outlet, in “Uplift” position without automatic return to “Neutral” position.

**ATTENTION:** WHEN OPERATING WITH THE USE OF THE MENTIONED VALVE IN THE POSITION “UPLIFT” DON'T FORGET TO SET THE VALVE CONTROL LEVER INTO “NEUTRAL” POSITION AFTER COMPLETION OF THE OPERATION IN ORDER TO PROTECT THE HYDRAULIC SYSTEM FROM OVERHEATING AND PREMATURE FAILURE OF THE PUMP AND OTHER UNITS OF THE HYDRAULIC SYSTEM!

3 Unit “11. Adjusting parameters”, “Hydraulic lift linkage” shall be amended as follows:

- the information available: “The pressure of distributor valve automatic return to neutral position is 15,5...20MPa.”
- shall be replaced with: “The pressure of automatic return of valves of a distributor P80-3/4-222 and P80-3/1-222 to “Neutral” position is from 16,5 to 20 MPa.”